

Application :			Technical Data Sheet of UnBleached Kraft								
Bakery Bags, Food items Packing,											
Grocery Bags											
			GSM Range			32 GSM - 80 GSM					
			Grade Name			BBR (BROWN BAG RIBBED) MBR(MIDDLE EAST BAG PLAIN)					
Parameters	Units	Test Method	GSM Range								
			32	38	40	45	50	60	65	70	
Avg.Brust Factor	Min.	(T 403 os -76)	22	22	24	24	25	25	25	25	
Average Tear Factor	Min.	(T 414 om – 82)	50	50	55	55	55	55	55	55	
Avg. Tensile Strength	Min. (Kg./15mm)	(T 404 om -82)	1.8	2.3	2.4	2.7	3	3.6	3.9	4	
Breaking Length	Min. (Meter)	(T 404 om -82)	4000	4000	4000	4000	4000	4000	4000	4000	
Cobb - 60	g./m ² (max)	(T 441 om – 82)	30	30	30	30	30	30	30	30	
Moisture	Min (%)	(T 412 om – 88)	5±0.5	5±0.5	5±0.5	5±0.5	5.0±0.5	6.0±0.5	6.5±0.5	6.5±0.5	
Issued By		Head Technical Services						Document No.			
Signature								Total Pages		1	
Issue Date		30-Sep-22						Version No		1	
								Revision No		75	