

Matt 80 / SP123 / WK80

Facestock

Matt 80

Description Matt coated woodfree paper.

Applications Standard label applications with matt finish.

Printing techniques Suitable for printing on laser, flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping.

| Property | Norm | Units | Value | Tolerance |
|-----------------|------------|------------------|-------|-----------|
| Substance | ISO 536 | g/m ² | 80 | ± 4% |
| Thickness | ISO 534 | µm | 74 | ± 4% |
| Bekk smoothness | ISO 5627 | s | ≤100 | |
| Brightness ISO | ISO 2470-2 | % | 96 | ± 2 |
| Whiteness CIE | ISO 11475 | % | 119 | ± 3 |
| Opacity | ISO 2471 | % | 90 | -2 |

Adhesive

SP123

Description Acrylic super-permanent adhesive with high tack. For difficult surfaces such as wood, some cardboards and plastics such as HDPE, PP, PET and PVC.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%

| Property | Norm | Units | Value | Tolerance |
|--|-------|--------|-------|-----------|
| Adhesion (Peel 180° 20'/stainless steel) | FTM 1 | N/25mm | 17,2 | ≥ 13,5 |
| Shear (1kg, in ² /glass) | FTM 8 | min | 100 | ≥ 60 |
| Tack (Quick Stick stainless steel) | FTM 9 | N | 11 | ≥ 9,8 |
| Minimum labelling temperature | | °C | +5 | |
| Minimum service temperature | | °C | -20 | |
| Maximum service temperature. | | °C | +80 | |

Liner

WK80

Description One-side coated white liner with good lay-flat characteristics. Suitable for sheeting. Available only in solid back

Color White

| Property | Norm | Units | Value | Tolerance |
|------------------------|------------|------------------|---------|-----------|
| Substance | ISO 536 | g/m ² | 80 | ± 4% |
| Thickness | ISO 534 | µm | 81 | ± 4 |
| Tensile strength MD/CD | ISO 1924-2 | kN/m | 4,6/2,3 | -0,6/-0,3 |

Certificates

Product approvals and usage certificates

Facestock

Matt 80

EN 1230 Sensorial analysis

Toy safety European directive 2009/48/CE

Packaging and packaging waste Directive 94/62/CE

Electric and electronic equipment (RoHS)

Adhesive

SP123

EN 71-3 Toy safety

EN 71-9 Toy safety

Packaging and packaging waste Directive 94/62/CE

German Recommendation BfR XIV (ISEGA) - Adhesives

Liner

WK80

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

- Values are subject to change without notice. Last updated 4/5/2016.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive is certified to the strictest environmental standards ISO 9001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and OHSAS 18001. Adestor products are available with PEFC™ and FSC® chain of custody certificates upon request.